

Special issue!



The **Extru-Technician**

Celebrating five years of sharing extrusion expertise in 2012

July 2012

Extru-TechInc.com

STRATEGIC CRITICAL CONTROL POINT SELECTION

"Remember, upon the conduct of each depends the fate of us all." Alexander the Great applied this philosophy to all disciplines of his life, whether in the execution of his military strategies and politics or in deliberation of the many challenges of his life. He knew that every problem, regardless of complexity, is influenced by multiple factors that each must be deliberated in terms of individual and collective synergy.

story continues on page 2



PHOTO: RMARMION | DREAMSTIME.COM

STRATEGIC CRITICAL CONTROL POINT SELECTION

As we continue our deliberation of petfood safety's Gordian Knot, this issue will discuss the impact of selecting the extruder (specifically the discharge point or die) as the critical control point (CCP) for various microbiologicals (i.e., *Salmonella*). If we first consider the typical validation constraints of most validation studies, the destruction and survivability of bacteria within a process are measured against time and temperature. Considering these parameters, the extruder presents probably the best model as a microbiological CCP for a typical dry-expanded petfood process. This is due to the predictable, consistent and measurable nature of the extruder's retention time, as well as the typical cooking temperature required for the production of most grain-based petfoods.

Retention time

Because the extruder is essentially a

high-pressure pump with sharp first in, first out (FIFO) characteristics, the retention time can be easily verified with a simple marker and sample capture scheme (dosing the inlet of the extruder with a colorant and recording time delays for color changes at the die). Typically, Extru-Tech will recommend that this be done while in production and at a steady state of operations. For a more scientific approach, the inoculation of a chemical marker followed by concentration analysis of a large sampling regiment is more than adequate.

The most prominent benefit to the extruder's residence time distribution profile, when compared to that of the symmetrical preconditioner, is its insulation from retention time fluctuations due to raw material changes (intentional or otherwise). Previous internal studies performed by Extru-Tech have proven, within the preconditioner, that when typical

The **Extru-Technician**

brought to you by **Extru-Tech Inc.**



CORPORATE OFFICE

PO Box 8, 100 Airport Road,
Sabetha, KS 66534
+1.785.284.2153 Tel
+1.785.284.3143 Fax
extru-technic@extru-technic.com
www.extru-technic.com

ADMINISTRATIVE STAFF

LaVon Wenger President/CEO
Don Wenger Executive Vice President
R. Scott Krebs Executive VP/COO

EQUIPMENT SALES STAFF

Bill Huseby
Director of North America Sales
billh@extru-technic.com +1.913.522.9014
Bob Annan Director of European Sales
boba@extru-technic.com +1.785.284.2153
Oswaldo Munoz
Director of Latin America Sales
oswaldom@extru-technic.com
+56.2.955.25.74 Santiago-Chile

Enzhi Michael Cheng, PhD,

Director of Asia Sales
michaelc@extru-technic.com
+1.785.285.0703

Doug Coverdale

Sales Engineer
doug@extru-technic.com
+1.785.284.2153

MARKETING & EDITORIAL STAFF

Norm Schmitt Corporate Sales Manager
norms@extru-technic.com
+1.785.284.2153

Will Henry

Technical Sales Engineer
willh@extru-technic.com
+1.785.284.2153

EXTRU-TECH, INC. PART SALES STAFF

Darryl Becker
darrylb@extru-technic.com
+1.785.284.2153

Mike Dunlap

miked@extru-technic.com
+1.785.284.2153

A WATT/Petfood Industry
custom publication

Gordian Knot

To read more about strategic selection of critical control points, see the [March issue of *The Extrusion Technician*](#).

processing additives are varied (i.e., steam, water, fat), the retention time also changes. The same influence can be seen in the extruder, but at a much lower magnitude.

Temperature

Reviewing the destruction of various microbiologicals, it is recognized that 172 degrees F (78 degrees C) provides for an almost instant control of most enterobacteria, including *Salmonella* (Fung 2008, "Synopsis of Food Microbiology"). Temperature control at this level in the extruder is almost guaranteed due to the mechanical and processing characteristics typically experienced with a dry-expanded petfood.

CCP event management

It is important to review all aspects of the process when considering CCP locations, especially the corrective actions required to recover from a CCP violation event (i.e., process parameter operating outside the criteria of a critical limit). Most likely, a CCP violation will require that all production within the time frame of said violation be quarantined from the process and destroyed. If we contemplate these actions with a

plan that utilizes the preconditioner as the CCP for *Salmonella*, provisions would be required to allow for safe quarantine and containment of the finely ground, under-processed material. Needless to say, this is not a trivial design task and offers minimal risk mitigation of recontamination when compared to other options.

However, if we take a similar CCP violation event with a plan that has utilized the extruder as the CCP, the corrective actions design is quite different as the state of the material has most likely been formed into much larger kibbles that should quarantine much easier with a greatly reduced risk of cross-contamination.

The need for science

When evaluating the continuous cooking extruder system for validation of the CCP associated with the pathogen kill step, the extruder consistently produces the highest degree of reliability associated with the pathogen kill step CCP. Although this publication places much emphasis on simple methods to determine extruder barrel residence time and temperature, the most effective and acceptable method to reliably validate the pathogen kill step CCP is through

STRATEGIC CRITICAL CONTROL POINT SELECTION

continued

a controlled scientific validation study. These studies involve the intentional inoculation of formulas with the target naturally occurring pathogens (not surrogates) at highly defined elevated contamination levels and the application of the intervention under evaluation. The microbial reductions associated with the intervention are then calculated to validate that indeed the pathogen kill step did occur prior to discharge of extrudate from the extruder.

Having identified the petfood manufacturer's need to reduce risk through controlled scientific validation studies, Extru-Tech has established a Food Safety Validation Extrusion Lab dedicated specifically to perform these types of tests. So the question is, as a petfood manufacturer, what level of confidence do you need to ensure that you are indeed doing everything possible to consistently manufacture high quality and safe petfood at the lowest risk to your consumers and brand?

The **Extru-Technician**

Your drying and extrusion resource



Have the next issue delivered directly to your inbox. Just click [here](#) to subscribe.

(Or visit http://eforms.kmpsgroup.com/wattpub/forms/extr_subscribe.htm)



YOU'RE
MISSING
**A KEY
PIECE...**

IN YOUR
**FOOD
SAFETY**
CERTIFICATION
PROCESS.



CORPORATE OFFICE
P.O. Box 8 • 100 Airport Road
Sabetha, KS 66534, USA
Phone: 785-284-2153
Fax: 785-284-3143
extru-techinc@extru-techinc.com
www.extru-techinc.com

BEST IN CLASS
**FOOD
SAFETY**

**EXTRUSION
VALIDATION**



CORPORATE OFFICE
P.O. Box 8 • 100 Airport Road
Sabetha, KS 66534, USA
Phone: 785-284-2153
Fax: 785-284-3143
extru-techinc@extru-techinc.com
www.extru-techinc.com

EXTRU-TECH.
YOUR TRUSTED
PARTNER FOR
**PETFOOD
SAFETY**

- **Validation Lab** - Dedicated ETI Production Scale Equipment
- **Validation Services** - Tailored and Product Based
- **Natural Pathogens** - None are Man-Made
- **Validation Master Plan** - Development & Implementation
- **Food Safety Assessments**
- **In-Plant Validation/Verification** - Protocol and Program Services
- **Process Microbial Mapping** - Pre and Post Validation
- **Project Management & Process Design**
- **Training** - Before, During & After Certification

The Extru-Tech Team includes personnel with expertise in: Quality Assurance, Facility and Process Engineering, Extrusion Manufacturing, Microbiology, Material Handling, Technical Services, Research & Development and Regulatory Affairs. Contact us today for details.



CORPORATE OFFICE
P.O. Box 8 • 100 Airport Road
Sabetha, KS 66534, USA
Phone: 785-284-2153
Fax: 785-284-3143
extru-techinc@extru-techinc.com
www.extru-techinc.com